

Oil and Gas Specialty Rental



TwinAir

Oil-injected Air Compressor 25 bar(g)



Atlas Copco

TwinAir Oil-injected Air Compressor 25 bar(g)

Principal Data

General	
Dimensions LxWxH (mm)	6.060 x 2.440 x 2.590
Mass dry/wet (kg)	14.950 / 16.470
Fuel tank capacity (l)	1.800
Sound pressure level LPA (7m) dB (A)	76
Sound power level LWA dB (A)	104

Engine	ALFA	+	BRAVO	TwinAir
Engine make	Caterpillar		Caterpillar	Caterpillar
Type	C13		C13	C13
Output (kW)	328		328	656
Fuel consumption at 100% load (l/h)	75		75	150

Compressor			
Maximum capacity FAD l/s	453	453	906
Maximum capacity FAD m ³ /min	27	27	54
Maximum capacity FAD cfm	960	960	1.920

Performance		Free Air Delivery		
Working Pressure		m ³ /min	m ³ /h	cfm
bar(e)	psig			
25	365	54,4	3.264	1.920

Other Features

- Integrated aftercooler (10°C + A)
- Spillage free frame
- Weather proof canopy
- Containerized
- DNV 271 lifting compliant
- Spark arrestor
- Overspeed shut down system
- Flame resistant anti static fan belts
- Fuel cut-off valve

Options

- AMES: Fire detection and automatic extinguisher.
- EEX (d) starters
- EX emergency stops



www.atlascopco.com/rental

2956 0190 00 - Subject to alteration without notice. Printed in Belgium. Copyright 2007, Atlas Copco Airpower n.v., Wilrijk, Belgium.

Atlas Copco